

## Duct Rodders

### Product Introduction:

A high quality fiberglass rod, specially constructed to provide exceptionally high tensile strengths, whilst retaining flexibility. The 80% fill rate glass fibre core is reinforced with a high strength resin. A braided reinforcing wrap is added before the final polypropylene wear resistant protective coating is applied. The continuous rods range from 4.5mm – 16mm with lengths from 20 metres – 400 metres.

### Pictures:



### Features:

- 1) Strong non-conductive fiberglass rod construction.
- 2) Rustproof bull-nose pulling eye.
- 3) For longer conduit runs and underground duct.
- 4) Rugged tubular steel reel with adjustable positioning.
- 5) Feed device allows rod to feed out or be wound back onto reel with easy push or pull of rod.
- 6) Many applications, both commercial and residential.
- 7) Splice kits and Repair Kits are available

### Technical Parameters:

Color		WHITE, YELLOW, RED, GREEN, BLACK, ORENGE, BLUE							
Frame color		BLACK、 SILVERY WHITE、 BLUE、 RED							
SIZE		870mm×400mm×920mm、 1200mm×400mm×1260mm、 1300mm×550mm×1360mm、 400mm×162mm×520mm。							
Type	1	2	3	4	5	6	7	8	9
Diameter (mm)	4	6	8	9	10	11	12	13	14
Weight(kg)	500	770	1560	2150	2500	2800	3100	4400	4600
Min. bend radius(mm)	140	190	220	260	330	390	450	500	550
Temperature		-40℃~+40℃							

\* The parameters are typical values and should be adjusted according to the actual situation.