

## GPJ-L Dome Fiber Optic Splice Closure

### Description:

Fiber Optic Splice Closures are made of high density reinforced PC material, can be used for aerial, underground, man-hole, duct and pole.

Speed Optic' s closures can be divided into two series: horizontal type and dome type. As for dome type, according to the sealing ways, including shrinkable dome closure and mechanical dome closure.

### Picture:



### Characteristics:

1. 7 inlet/outlet ports and heat shrinkable fixing sleeve should be ordered in addition according to actual requirement.
  2. The fittings provided: 1 piece of wrench, earthing wire, nylon tie, labeling paper, desiccant, aluminum-foil paper.
  3. Accessories for customers' selection: buffer tube for bunchy fiber, buffer tube for ribbon fiber, earthing deriving device, pressure testing valve, small heat shrinkable fixing sleeve and big heat shrinkable fixing sleeve and 1 set of metal hoop.
- It suits for straight-through fiber cable and branching fiber cable at the same time.

### Specifications:

Model	Size (mm) H×D	Core capacity	Cable Port (max)	Max diameter of cable (mm)	Core capacity per tray	Sealing Type
GPJ-L-I (bunchy)	455×220	120-240	7	6XØ21	12-24	Shrinkable
GPJ-L-II (ribbon)		576		1XØ36	72	