


MPO Patchcord

Description:

All industry standard fiber optic connectivity together with customized connectors are available for terminating to all kinds of patchcord and/or pigtail at different lengths. With great in-house manufacturing of fiber optic connector, cable and cable assembly, it provides the advantages of flexibility, superior quality and quick turn-around.

Picture:



Features:

- Low insertion loss, high return loss.
- High precision guide pins for exact alignment.

Applications:

• FTTB, 40G/100G SFP, SFP+, QSFP.

Specifications:

opecinications.					
Parameter	Unit	Index			
Fiber Type	1	G652B, G652D, G655, G657A1, G657A2,			
Fiber Type	ı	A1a, A1b, OM3, OM4			
		SM Standard	SM Lowloss	MM Standard	MM Lowloss
Insertion Ty	/p dB	0.35	0.3	0.35	0.2
Loss Ma	ах	0.75	0.35	0.65	0.35
Return Loss	dB	APC≥50	1	≥25	≥35
Return Loss	uв	PC≷40			
Repeatability	dB	≤0.1			
Interchangeabil	ity dB	≤0.3 (Connector Randomly)			
Durability	dB	≤0.3 (change 500 matings)		≤0.3 (change 1000 matings)	
Vibration	dB	≤0.3 (10~55Hz)			
Operating	$^{\circ}\!\mathbb{C}$	-25~+70			
Temperature	C				